



1425 Highland Avenue (Rt. 10) P.O. Box 728
 Cheshire, CT 06410 - 1216 U.S.A.
 Phone # 203 - 272 - 3234
 Fax # 203 - 271 - 0352
 E - mail: Sales@microtech-inc.com
 Visit our Web site: <http://www.microtech-inc.com>

RECTANGULAR RIGID WAVEGUIDE SPECIFICATIONS

TYPICAL ELECTRICAL SPECIFICATIONS							
EIA WR SIZE	FREQUENCY RANGE (GHz)	MRH ALUMINUM		MRC OFHC COPPER		MRF COMMERCIAL BRONZE	
		*VSWR	**ATTEN.	*VSWR	**ATTEN.	*VSWR	**ATTEN.
22	33.00-50.00	1.05	0.485	1.05	0.310	N/A	
28	26.50-40.00	1.05	0.344	1.05	0.219		
42	18.00-26.50	1.04	0.207	1.04	0.132		
62	12.40-18.00	1.04	0.097	1.04	0.062	1.04	0.085
75	10.00-15.00	1.03	0.077	1.03	0.049	1.03	0.062
90	8.20-12.40	1.03	0.065	1.03	0.041	1.03	0.056
102	7.00-11.00	1.03	0.054	1.03	0.034	1.03	0.048
112	7.05-10.00	1.03	0.042	1.03	0.027	1.03	0.037
137	5.85-8.20	1.02	0.030	1.02	0.019	1.02	0.029
159	4.90-7.05	1.02	0.023	1.02	0.015	1.02	0.020
187	3.95-5.85	1.02	0.021	1.02	0.013	1.02	0.019
229	3.30-4.90	1.02	0.014	1.02	0.009	1.02	0.012
284	2.60-3.95	1.02	0.011	1.02	0.007	1.02	0.009
340	2.20-3.30	1.02	0.009	1.02	0.006	N/A	N/A
430	1.70-2.60	1.02	0.006	1.02	0.004	N/A	N/A
650	1.12-1.70	1.02	0.003	1.02	0.002	N/A	N/A
* VSWR is per 2 Foot Section ** Attenuation is in dB per Foot							

[Ask about Double-ridge Rigid Waveguide and Millimeter Rigid Waveguide.](#)